

# Loader Ground Engaging Tools



## Extend GET wear life and improve loader productivity

Our range of loader Ground Engaging Tools is designed to provide the optimum combination of strength, flexibility and wear resistance for particular applications and environments:-

- Produced in either high carbon or heat treated boron steel with Brinell hardness in range 430-530HB.
- Variable thicknesses available to suit application and maintenance schedules.
- Deep countersinks for strong fit and bolt protection.

### Spade Edges



Provides extra penetration in rock and heavy material for heavy-duty rock buckets. Ready drilled for easy fitting of wear blades and teeth.

### Double Bevel Edges



Supplied as weld in base edges to give buckets added strength. Bolt on replacement under blades provide easy change over and extended wear life.

### Heel Plates



Provides additional strength to rear underside of the bucket, extending wear life and reducing frequency of bucket changes.

### Segments



Provides additional protection and wear life when fitted between adapters. Available in flat reversible or half arrow variants for additional durability.

### Toe Plates (Base Edges)



Standard or custom made weld-in-base edge designs can be made to suit all types of buckets and applications.

### Side Cutters



Blademaster side cutters provide additional strength to the walls of a bucket and enable it to accept corner adapters and wear protection shrouds.

## Select the right tool for the job

Our Loader GET are designed as an integrated system to maximise productivity in specific applications and site conditions. Use our Loader Application Guide to help you select the right tools for the job.

Application and Material	Blademaster General Duty	Xtreme Heavy Duty	Xtreme Very Heavy Duty	Xtreme Tough	Xtreme Sub Zero
<b>Light material handling, stockpiling &amp; loading:</b> Low impact and abrasion material : grain, wood chip, refuse etc.					
<b>General duty bank loading, digging &amp; stockpile loading:</b> Low/moderate abrasion & low impact material; soil, gravel.					
<b>High Abrasion Material Loading:</b> Highly abrasive but low to moderate impact granular and broken material.					
<b>High Abrasion and High Impact Material Loading:</b> Digging and loading larger sized angular rocks with high impact.					
<b>Extreme Cold Weather Applications:</b> High abrasion and/or high impact applications in temperatures down to -50°C.					

To find out more:

Call us: +44 (0)1207 230621

Email us: [info@conmecheng.com](mailto:info@conmecheng.com)

Visit us: [www.conmecheng.com](http://www.conmecheng.com)